



ASD02 and ASD08

Description

Where a public address (PAGA) system is installed to provide broadcast of potentially life saving emergency speech and alarm tone signals a high integrity configuration is required. This also extends to the AC mains supply energising the PAGA package.

For additional security it is possible to duplicate AC mains supply inputs "PRIMARY" and "SECONDARY" thereby ensuring continued PAGA capability in event of failure of either AC supply input.

The BARTEC VODEC ASD02 automatically manages the selection of AC mains supply inputs and provides the engineer with details status display on a "front of rack" LED annunciator panel type ASD08.

The ASD02 provides eight independently fuse protected outputs. Which are assigned to VA300+PSU, amplifier power supply units, flashing beacon power supply and auxiliary devices.

The ASD sub-system comprises of two parts i.e. ASD02 is a clip on/off DIN rail mounted assembly which facilitates termination mains supply inputs.

The ASD08 power management LED annunciator comprises of a low profile 1 unit high 19 inch rack mount panel.

With an integral display window it is fitted with secondary fault reporting contacts to enable possible interface to the site DCS/ SCADA/ Telecom supervisory package.

On board high power supply management ensures galvanic isolation between the primary/secondary AC mains supply inputs and facilitates priority selection of online/standby power supply source.

The ASD02 carries on board neon indicator sets to facilitate rapid fault finding and service and dedicated high rupture capacity cartridge fuses provide supervised protection for each supply output.

Display is extended from the ASD002 via optically isolated outputs which control a rack mount ASD08 LED annunciator display units.

A tamper proof test switch is fitted to ASD02 to enable the engineer to manually check the operation of the target PAGA system on the hot-standby mains supply.

Features

- High security applications
- On board fuse protection for each outlet
- Detailed diagnostic display monitors fuses, each input, each output
- No break "bump free" power supply autonomy
- Diversity of supply and simple maintenance/service
- Rapid fault finding simplified service minimal down time

Technical Data

ASD02

Dimensions

500 mm deep
150 mm wide
100 mm high

Weight

2 kg

Temperature range

-20 °C to +60 °C

Capacity

8 x supervised outlets each rated 25 A total module capacity is 125 A

Supply voltage

110/120 V AC 50/50 Hz

ASD08

Dimensions

483 mm wide (19" rack mount)
44.5 mm high (1 unit)
50 mm deep

Weight

0.5 kg

Temperature range

-20 °C to +50 °C

Capacity

2 x ASD02 module

Supply voltage

48 C DC derived from VX/AT host management system or VA300/CAGE

